

AUSTRAL MARINE to be used/installed as specified.

Plywood to be manufactured with timber species: **Araucaria (Hoop Pine)**.

Face and back veneer grades to be **AA or OO**, conforming to Australian Standards for veneer grading.

Core grade to be **A Multiply**, conforming to Australian Standards for veneer grading.

Glue system to be used is **A-Bond Phenolic (black glueline)** with formaldehyde emissions rating of **Super E0**, tested in accordance with AS/NZS 2098.11 : 2005. Manufacturer warranty on glue bond to be **25** years.

Plywood supplied must be manufactured to Australian Standard **AS/NZS 2272:2006** and be certified under the **EWPA JAS-ANZ** Product Certification Scheme. Plywood must also be Green Star rated and be environmentally certified to **RW/PEFC**.

Plywood to be certified Fire Group **3** per BCA Specification C1.10 clause 4.

Plywood to conform to Stress Grade **F17** (or better), in accordance with AS/NZS 2269.1.

Panel size to be **2400 x 1200, 2700 x 1200mm** (delete as required).

Panel thickness to be **4, 6.5, 9, 12, 15, 18, 24, 30mm** (delete as required).

<http://www.australply.com.au/austral-marine>

Contact: Austral Plywoods Sales - sales@australply.com.au - 07 34268666



**AUSTRAL
PLYWOODS**

07 3426 8666
sales@australply.com.au
www.australply.com.au

*100% Australian
made, since 1925*