



**AUSTRAL
PLYWOODS**

Products - General Information

Hoop Pine

Austral Plywoods manufactures plywood from 100% Australian grown plantation [Hoop Pine](#). A labour intensive selection process strives to achieve the highest quality faced plywood within each product category.

F17 Stress Grade

Our structural, marine and exterior products are rated with a stress grade of F17. This superior stress grade is attributable to our premium Hoop Pine resource, the efficient utilisation of that resource, and a commitment to quality manufacture. (The Exterior standard, AS/NZS 2271, does not allow the designation of stress grades, however our exterior products also comply with the Structural standard AS/NZS 2269 F17 stress grade rating.)



Low Formaldehyde Emissions

We utilise glue systems that are low in formaldehyde. EWPA testing has permitted us to label our products with an E0 rating, the lowest obtainable.

Available Dimensions

We have the largest range of panel sizes and thicknesses. The standard dimensions generally available are:

Length	2400 and 2700mm
Width	900 and 1200mm
Thickness	Thicknesses range from 1.5mm to 32mm, with thicknesses exceeding 32mm available on request.

With this large range we can offer a cost effective solution for your customers' special requirements.

Quality Assured

Austral Plywoods manufactures according to the requirements of the [EWPA-AJAS-ANZ quality control and product certification](#) scheme. Purchasers thus can have confidence in the quality of the product.